



BAYLAN BT-RF MODEM

TECHNICAL SPECIFICATIONS

1-) CHARACTERISTICS OF HANDHELD DEVICE

- Powered by an internal rechargeable battery.
- Average operating current consumption is between 70 mA and 80 mA.
- ARM core is used as processor.
- 2 LEDs provide information during data flow and charging operation.
- The average working time is 24 hours with a full charge.



1-A) BLE MODULE PROPERTIES

- Compatible with Bluetooth® v5.1, ETSI EN 300
- The maximum data rate is 57600 kbps
- Pairing and connection distance with BT device is maximum 10 m.

1-B) RF MODULE FEATURES

- Center Frequency: 868.03 MHz and support to whole wM-Bus frequency channel
- EU compatible license-free 868 MHz ISM / SRD band
- Channel Interval: 59.9 KHz
- Modulation: GFSK, FSK
- Frequency Deviation: Adjustment to wM-Bus standart bandwidth
- Data Rate: 38.4 kbps , 100 kbps (wM-Bus)
- Transmitter power: 14 dBm (25 mW)
- Transmitter current consumption: 32mA
- Receiver bandwidth: 102 kHz (Receiver is configured for Handheld terminal)
- Crystal Frequency: 32 Mhz +/- 10ppm
- Distance: 750 meters in open area and sight distance (according to installation instructions)

2-) WORKING PRINCIPLE OF THE COLLECTOR UNIT

Reading the number, consumption, and status information of BAYLAN RF meters located in a 750 mt circle and transmitting the information is the aim of Baylan BT Device.

When the collector is turned on, buzzer sound will be heard 3 times. The BT unit will be ready for connection by another device within 20 seconds. After succesful connection BT Device Collecting RF signals is started.

3-) CHARGING OF THE COLLECTOR UNIT

Baylan BT Device unit is charged with USB port. Charge power is DC 5V, 250mA. Any desktop computer, laptop computer, or universal USB charger will suffice to charge the charging unit. Maximum charging duration is 12 hours. The information LED, which is near to the USB port, lights up during charging. LED will be turned off, when charging is completed. You can continue to use your device during charging. The device can be used for 24 hours with a full charge.

4-) FUNCTIONAL PROPERTIES

- The communication between BT Device and the mobile device has legacy pairing security mechanism.
- Supports wM-Bus T mode in standard EN13757-3.
- Supports special Baylan Water Meters RF protocols.
- Audible warning can be given at the time of RF communication.
- LED can be signaled at the time of RF communication.

5-) ENVIRONMENTAL PROPERTIES

- Operating temperature: from -20 °C to +70 °C
- Relative humidity: 5% - 95% (non-condensing)
- Dimensions: 110mm x 75mm x 25mm
- Weight: 250 grams

BAYLAN ÖLÇÜ ALETLERİ SAN. VE TİC. A.Ş.

Factory: A.O.S.B. 10032 Sk. No:16 Ciğli - İZMİR / TÜRKİYE

Tel: +90 (232) 497 97 00 • Fax: +90 (232) 497 97 51 - 497 97 52 - 497 97 53

e-mail: info@baylanwatermeters.com • web: www.baylanwatermeters.com